



2.5/4KW

Specifications:

Lamp Power: 2.5/4KW-standard model(All power settings are auto selecting)

Input Voltage: 90-250V 50/60Hz

Input Current: 35A

Efficiency: 93%

Power Factor: 0.98

Dimensions: 9.5" W X 14" H X 17.7" L

Max Ambient Temp: 113° F

Weight: 37.4 lb

LED Indicators: Power Lamp Temp Flicker Free 60Hz 50Hz

Controls: Stop Start Dimmer

Features: Automatic power selecting single

Temperature controlled fan cooling

Diagnostic protection:

-Over voltage

-Low voltage

-Over current

-Earth current

-Output short

-Over temperature

Very rugged construction

818.843.4560 sales@cinemills.com



575/1200W

Specifications:

Lamp Power: 575/1200W-standard model(All power settings are auto selecting)

Input Voltage: 90-125/180-250V 50/60Hz

Input Current: 25-18A/13-9A

Efficiency: 93%

Power Factor: 0.68

Dimensions: 7.8"W X5.9" H X 11.8" L

Max Ambient Temp: 113° F

Weight: Appro 15 lb

LED Indicators: Power Lamp Temp Flicker Free 60Hz 50Hz

Controls: Stop Start Dimmer

Features: Automatic power selecting single

Temperature controlled fan cooling

Diagnostic protection:

-Over voltage

-Low voltage

-Over current

-Earth current

-Output short

-Over temperature

Very rugged construction

818.843.4560 sales@cinemills.com



200W

Specifications:

Lamp Power: 200W-standard model
Input Voltage: 90-125/180-250V 50/60Hz
Input Current: 2-1.6A
Efficiency: 93%
Power Factor: 0.68
Dimensions: 6.4" W X 5.3" H X 9.2" L
Max Ambient Temp: 113° F
Weight: 6.6 lb
LED Indicators: Power Lamp Temp
Controls: Stop Start Dimmer

Features: Automatic power selecting single

Temperature controlled fan cooling

Diagnostic protection:

- Over voltage
- Low voltage
- Over current
- Earth current
- Output short
- Over temperature

Very rugged construction

818.843.4560 sales@cinemills.com